

## HAF Stir Fan with Wide Guard

### Features

- Wide guard spacing reduces buildup and allows for easy cleaning so your fan remains efficient
- Promotes uniform temperatures throughout your building
- Maximum air circulation with minimal power usage
- Reduce stratification and promote uniform air circulation
- Versatile mounting bracket allows for tilt and swivel of fan to easily change direction and angle of air movement
- Totally enclosed, maintenance-free, direct drive high-efficiency motors have completely sealed ball bearings, and are covered by a **Two Year Warranty**
- Attached 10' cord with 3-prong plug pre-wired for 115 Volt (electrician may rewire for 230 Volts)
- Pair with a J&D variable speed control for maximum flexibility and efficiency



VS18

No electrician needed!  
**Hang it up  
Plug it in**



VS188

Part#	Size	Ph	Spd	Thrust CFM	Thrust CFM/ Watt	Drive	Prop
<b>Single Phase</b>							
VS18	18"	1	1/Var^	1,880	18.8	Direct	3-Alm
VS188	18"	1	1	1,820	19.5	Direct	3-Alm
VS183	18"	1	3	<b>1,770</b>	<b>17.7</b>	Direct	3-Alm
				<b>1,450</b>	<b>22.0</b>		
				<b>1,180</b>	<b>22.7</b>		
VS20	20"	1	1/Var^	1,890	20.3	Direct	3-Alm
VS203	20"	1	1/Var^	<b>3,810</b>	<b>11.4</b>	Direct	3-Alm
VS24	24"	1	1/Var^	<b>3,790</b>	<b>13.1</b>	Direct	3-Alm
VS242	24"	1	1/Var^	<b>5,630</b>	<b>12.8</b>	Direct	3-Alm

^ Variable speed fans require separate variable speed control to adjust fan speed.

**Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12**

OSHA requires this fan to be mounted a minimum of 7' above the floor

**⚠ WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov/product](http://www.P65Warnings.ca.gov/product).

Due to our continual effort to provide the best products available and adhere to market conditions; literature, products, prices and availability are subject to change without notice.