

Mega Storm

72" Fiberglass Exhaust Fan



Features

- Certified performances up to 41,029 CFM @.10" SP
- Single or three phase 3 HP, UL recognized motors
- Four-point contact X-frame for strength and durability
- UV resistant smooth molded fiberglass housing
- Twin Gates[®] size "A" belts are easily accessible and require no tools for replacement in seconds
- Double groove steel belt tensioner for longer life
- Quiet and smooth operation
- 5 bladed aluminum propeller
- Aluminum or poly shutters
- · Available with or without one-piece molded cone
- Heavy gauge stainless steel shutter clips
- 1½" shaft and sealed pillow block bearings
- Heavy duty guard is hot dip galvanized after welding
- Bottom motor location for easy access when installed
- Drainage holes in the bottom of the housing for moisture
- 2 Year Warranty on motors
- 3 Year Warranty on bearings
- 10 Year Warranty on propeller
- 20 Year Warranty on fiberglass housing



▲ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.

Due to our continual effort to provide the best products available and adhere to market conditions; literature, products, prices and availability are subject to change without notice.





Mega Storm

72" Fiberglass Exhaust Fan



Stainless steel heavy gauge shutter clips swivel by hand for easy removal of the shutter when it's time to clean or maintain your fan.

				@	@ 0.10" SP				
Doub #	C:	D.	C 4	CF		CFM/	Dutus	Duan	
Part #	Size	PN	Spd	CF	ΙΜ	Watt	Drive	Prop	
Single Phase					_				
No Cone Aluminum Shutter									
VMSA72A5N31	72"	1	1	20	264	11.9	Dolb	E Alm	
***************************************	/2	Ī	1	39,	364	11.9	Belt	5-Alm	
Poly Shutter	72"	1	1	20	264	11.0	Dalt	E Alm	
VMSP72A5N31	12	1	1	39,	364	11.9	Belt	5-Alm	
With Cone									
Aluminum Shutte		1	1	44.4	220	142	Dalt	ГАІна	
VMSA72A5C31	72"	1	1	41,0	029	14.3	Belt	5-Alm	
Poly Shutter	I 70"					444	D 11	E AL	
VMSP72A5C31	72"	1	1	39,	560	14.1	Belt	5-Alm	
Three Phase		_			_				
No Cone									
Aluminum Shutte		_		- 20	264	110	D 11	E AL	
VMSA72A5N33	72"	3	1	39,	364	11.9	Belt	5-Alm	
Poly Shutter	<i>"</i>				264	11.0	- I	E 41	
VMSP72A5N33	72"	3	1	39,	364	11.9	Belt	5-Alm	
With Cone									
Aluminum Shutte		_							
VMSA72A5C33	72"	3	1	42,	973	13.8	Belt	5-Alm	
Poly Shutter									
VMSP72A5C33	72"	3	1		973	13.8	Belt	5-Alm	
Bold red text is data based on testing Rough Opening									
performed by an accredited lab using ANSI/AMCA Standard 210-07						Side-By-Side Recommended OC Dimension for Fan with Cone Minimum 81"			



Twin Gates® size "A" belts are easily accessible and require no tools for replacement in seconds.



Heavy duty guard is hot dip galvanized after welding to protect from corrosion.

△WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.

Due to our continual effort to provide the best products available and adhere to market conditions; literature, products, prices and availability are subject to change without notice.

